

Trio Pines

Mobility Solutions . . . From The Ground Up!

Plex Wheels Solid Polyurethane

- A nice, round chunk of solid polyurethane.
- With 1-piece construction, there is no possibility of tread separation.
- Non-marking.
- Protects floors.
- High load capacities.
- Non-rusting and not affected by water, oil, and most chemicals.
- Temperature range -50° F to 180° F.
- Durometer -- 60 Shore D.
- Ideal for food service equipment, medical equipment, garages, etc.
- Blue is our standard color, but other colors are available -- just ask!



Plex

See other side for more information!

Plex Wheels

Solid Polyurethane



Plex Wheels	Wheel Diameter	Tread Width	Hub Length	Bearing Type	Load Capacity	List Price
#PLX-3K5	3"	1-1/4"	1-9/16"	1/2" Plain	300	\$ 4.78
#PLX-4K5	4"	1-1/4"	1-9/16"	1/2" Plain	400	\$ 8.73
#PLX-5K5	5"	1-1/4"	1-9/16"	1/2" Plain	700	\$ 12.53
#PLX-4M0	4"	2"	2-3/16"	(less brg)	700	\$ 12.53
#PLX-4M7	4"	2"	2-7/16"	Roller	700	\$ 14.48
#PLX-5M0	5"	2"	2-3/16"	(less brg)	800	\$ 17.25
#PLX-5M7	5"	2"	2-7/16"	Roller	800	\$ 19.23
#PLX-6M0	6"	2"	2-3/16"	(less brg)	900	\$ 23.08
#PLX-6M7	6"	2"	2-7/16"	Roller	900	\$ 25.00
#PLX-8M0	8"	2"	2-3/16"	(less brg)	1000	\$ 39.10
#PLX-8M7	8"	2"	2-7/16"	Roller	1000	\$ 41.03

Additional Available Bearings:

Delrin -- add DB to end of part number
 Precision Ball -- add PBB to end of part number
 Stainless Steel Precision Ball -- add PBS to end of part number
 Stainless Steel Roller -- add SS to end of part number

(Note: Not all bearings are available on all wheels. Please contact us for specific information.)