

RND

Round tread Rubber on Aluminum



Features

- *Soft Hi-modulus rubber tread chemically bonded to a strong aluminum core*
- *Capacities up to 1,000lbs.*
- *Temperature Range: -40°F to +180°F*
- *Hardness: 60-70 Shore A (±5)*

Wheel Diameter	Tread Width	Hub Length	Wheel Bearing	Bearing ID	Wheel Number	Load Capacity	Applicable Series
6	2	2-3/16	(less ball bearing)	1-3/8	RND-6M0	750	TP6660, TP6860, TP7060
			(less roller bearing)	1-3/16	RND-6M0-RB		
		2-7/16	Ball	1/2	RND-6M5		
			Ball	5/8	RND-6M6		
			Ball	3/4	RND-6M7		
			Precision Ball	1/2	RND-6M5-PBB		
Roller	3/4	RND-6M7-RB					
8	2	2-3/16	(less ball bearing)	1-3/8	RND-8M0	1000	TP6680, TP6880, TP7080
			(less roller bearing)	1-3/16	RND-8M0-RB		
		2-7/16	Ball	1/2	RND-8M5		
			Ball	5/8	RND-8M6		
			Ball	3/4	RND-8M7		
			Precision Ball	1/2	RND-8M5-PBB		
Roller	3/4	RND-8M7-RB					



www.TrioPines.com

L.A | 800-468-6987

DAL | 800-608-4676

CHI | 800-647-9991