

SDI

Ductile Iron



Features

- *Highly resistant to breakage even under heavy impact*
- *Ductile Iron material has a tensile strength of 40,000psi*
- *Capacities up to 6,000lbs.*
- *Temperature Range: -40°F to +800°F*

Wheel Diameter	Tread Width	Hub Length	Bearing ID	Wheel Bearing	Wheel Number	Load Capacity	Applicable Series
4	2	2-3/16	1-3/16	(w/o bearing)	SDI-4M0	1500	TP6640, TP6840, TP7040
		2-7/16	3/4	Roller	SDI-4M7		
5	2	2-3/16	1-3/16	(w/o bearing)	SDI-5M0	1500	TP6650, TP6850, TP7050
		2-7/16	3/4	Roller	SDI-5M7		
6	2	2-3/16	1-3/16	(w/o bearing)	SDI-6M0	2000	TP6660, TP6860, TP7060
		2-7/16	3/4	Roller	SDI-6M7		
	2-1/2	2-3/4	1-15/16	(w/o bearing)	SDI-6P0	3500	TP6960, TP7160, TP7260
		2-7/8	1	Roller	SDI-6P8		
	3	3-1/4	1-15/16	(w/o bearing)	SDI-6R0	6000	TP7560
		3-3/8	1	Roller	SDI-6R8		
8	2	2-3/16	1-3/16	(w/o bearing)	SDI-8M0	2000	TP6680, TP6880, TP7080
		2-7/16	3/4	Roller	SDI-8M7		
	2-1/2	2-3/4	1-15/16	(w/o bearing)	SDI-8P0	4000	TP6980, TP7180, TP7280
		2-7/8	1	Roller	SDI-8P8		
	3	3-1/4	1-15/16	(w/o bearing)	SDI-8R0	6000	TP7580
		3-3/8	1	Roller	SDI-8R8		
10	2-1/2	2-3/4	1-15/16	(w/o bearing)	SDI-10P0	4500	TP6910, TP7110, TP7210
		2-7/8	1	Roller	SDI-10P8		
	3	3-1/4	1-15/16	(w/o bearing)	SDI-10R0	6000	TP7510
		3-3/8	1	Roller	SDI-10R8		
12	3	3-1/4	1-15/16	(w/o bearing)	SDI-12R0	6000	TP7512
		3-3/8	1	Roller	SDI-12R8		



www.TrioPines.com

L.A | 800-468-6987

DAL | 800-608-4676

CHI | 800-647-9991