

RAL

Flat tread Rubber on Aluminum



Features

- *Non-Marking Soft Rubber tread chemically bonded to a strong core*
- *Capacities up to 800lbs.*
- *Temperature Range: -40°F to +160°F*
- *Hardness: 70-80 Shore A (±5)*

Wheel Diameter	Tread Width	Hub Length	Bearing ID	Wheel Bearing	Wheel Number	Load Capacity	Applicable Series
3-1/2	1-1/4	1-1/2	3/8	Annular Ball	RAL-35G3	250	TP5035, TP5235
4	1-1/4	1-1/2	3/8	Annular Ball	RAL-4G3	250	TP5040, TP5240
5	1-1/4	1-1/2	3/8	Annular Ball	RAL-5G3	275	TP5050, TP5250
6	2	2-3/16	1-3/16	(w/o bearing)	RAL-6M0	550	TP6660, TP6860, TP7060
		2-7/16	3/4	Roller	RAL-6M7		
8	2	2-3/16	1-3/16	(w/o bearing)	RAL-8M0	800	TP6680, TP6880, TP7080
		2-7/16	3/4	Roller	RAL-8M7		



www.TrioPines.com

L.A | 800-468-6987

DAL | 800-608-4676

CHI | 800-647-9991